

FOSHAN CIVRO WINDOWS, DOORS & CURTAIN WALL SYSTEM CO. LTD

TEST REPORT

REPORT NUMBER

180418002SHF-BP-1R1

ISSUE DATE

2018/7/9

REVISED DATE

2018/7/12


PAGES

13

DOCUMENT CONTROL NUMBER

LFT-APAC-SHF-OP-10a

© 2018 INTERTEK



Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1

Applicant: FOSHAN CIVRO WINDOWS, DOORS & CURTAIN WALL SYSTEM CO. LTD
 Applicant Address: Shishan Science & Technology Park, N. Xingye Road, Nanhai District, Foshan, China
 Attn: Evan Yuan
 Manufacturer: FOSHAN CIVRO WINDOWS, DOORS & CURTAIN WALL SYSTEM CO. LTD
 Manufacturer Address: Shishan Science & Technology Park, N. Xingye Road, Nanhai District, Foshan, China
 Attn: Evan Yuan
SUBJECT: Performance testing
 COD65 casement door

Dear Sir,

This test report for represents the results of our evaluation of the above referenced product(s) to the requirements contained in the following standards:

TEST METHODS AND STANDARDS
AS 2047-2014 Windows and external glazed doors in buildings (Amdt 2-2017)

SAMPLE ID	MODEL	SPECIFICATION
S180418002SHF.001	COD 65	1000 mm (W) x 2800 mm (H)

SAMPLE RECEIEVED: 2018/6/28
 TESTED FROM: 2018/7/3 TO 2018/7/3

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1

Test Items, Method and Results:

1 Test Samples

A full scale of sample was provided by the manufacturer that was not weathered nor conditioned.

The description of the samples given below has been prepared from information provided by the sponsor of the test. All values quoted are nominal, unless tolerances are given.

Table 1 Product Information

1	Product Name	COD65 casement door
2	Model	COD 65
3	Dimension of Window Frame	1000mm(width) x 2800mm (height) x 65mm (thickness)
4	Dimension of Window Sash	899mm (width) x 2738.5 (height) x 65 mm (thickness)
5	Profile (Aluminum)	Model:(1) CR14401, (2) CR14601 Supplier: Foshan CIVRO Windows, Doors & Curtain Wall System Co. Ltd
6	Frame Corner Construction Details: Joinery type	Frame: Mechanically assembled: Glued & Manually screwed Panel: Mechanically assembled: Glued
7	Reinforcement	None
8	Glazing	Dimension: 745mm (width) x 2584.5mm (height) Structure: 24mm thick 6mm + 12mm air + 6mm tempered insulating glass Supplier: Foshan CIVRO Windows, Doors & Curtain Wall System Co. Ltd
9	Hardware	Handle Model: 82000L Cylinder Model:881-35k-55 Hinge Model:3751600001 Supplier: Foshan CIVRO Windows, Doors & Curtain Wall System Co. Ltd
10	Weather Bar	Not applicable
11	Thermal Break	Model: 978700 Material: PA66 Supplier: Foshan CIVRO Windows, Doors & Curtain Wall System Co. Ltd
12	Drainage	Sizes: diameter 4mm quantity: 4
13	Gasket (between leaf and frame)	Model: (1)C36001, (2)35008, (3) 35053 Material: EPDM Supplier: Foshan CIVRO Windows, Doors & Curtain Wall System Co. Ltd
14	Sealant of Glass	NA
15	Installation	The exterior perimeter of the test specimen was sealed with silicon sealant

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1

Test Items, Method and Results:

2 Test Result

Table 2 Test Results

Test Description	Test Result		
Serviceability Design Wind Pressure AS/NZS 4420.1-2016 section 3	±	800	Pa
Deflection / Span Ratio Framing member 1	Stile at handle side	1/2373	
Deflection / Span Ratio Framing member 2	Rail at bottom	1/3775	
Operating Force AS/NZS 4420.1-2016 section 4	Initial Movement	54	N
	Maintain Movement	4	N
Air Infiltration at ±75 Pa AS/NZS 4420.1-2016 section 5	at +75Pa	0.95	L/s·m ²
	at -75Pa	1.27	L/s·m ²
Overall area: 2.80 m ²			
Water Penetration AS/NZS 4420.1-2016 section 6	No water penetration at	450	Pa or less
	Description: After sprayed for 3 minutes at 600 Pa, the water penetration started at the bottom of door leaf and frame.		
Ultimate Strength Test Pressure AS/NZS 4420.1-2016 section 7	+	2000	Pa with no collapse
	-	2000	Pa with no collapse
	Description: No significant breakage, permanent deformation or operational malfunction after ultimate strength was released.		

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1

Appendix A: Test Data and Sample Drawings:

A.1 Deflection Test – Test method AS/NZS 4420.1-2016

Test Pressure (Serviceability design wind pressure), P = 800 Pa, rating N4

Note: No structural members in a completely assembled and glazed window shall deflect by an amount greater than the following, when tested at the serviceability design wind pressure:

- (a) Span/250 for windows and sliding doors.
- (b) Span/100 for doors other than sliding.

Table 3 Test Data of Deflection Test

Member (mm)		Test Pressure (Pa)	Deflection (mm)			Actual Deflection	Deflection /Span Ratio
Item	Span Length		1	2	3		
Stile at handle side	2610	+P/4 = 200	0.3	0.3	0.1	0.1	1:26100
		+2P/4 = 400	0.6	0.6	0.2	0.2	1:13050
		+3P/4 = 600	1.0	1.1	0.4	0.4	1:6525
		+4P/4 = 800	1.3	1.5	0.5	0.6	1:4350
		0	0.0	0.1	0.0	0.1	1:26100
Stile at handle side	2610	-P/4 = -200	0.3	0.3	0.1	0.1	1:26100
		-2P/4 = -400	0.6	0.8	0.2	0.4	1:6525
		-3P/4 = -600	1.0	1.5	0.4	0.8	1:3263
		-4P/4 = -800	2.0	2.3	0.5	1.1	1:2373
		0	0.7	0.3	0.1	0.3	1:8700

Table 4 Test Data of Deflection Test

Member (mm)		Test Pressure (Pa)	Deflection (mm)			Actual Deflection	Deflection /Span Ratio
Item	Span Length		3	4	5		
Rail at bottom	755	+P/4 = 200	0.1	0.1	0.0	<0.1	<1:7550
		+2P/4 = 400	0.2	0.2	0.1	<0.1	<1:7550
		+3P/4 = 600	0.4	0.4	0.1	0.2	1:3775
		+4P/4 = 800	0.5	0.5	0.2	0.2	1:3775
		0	0.0	0.0	0.0	<0.1	<1:7550
Rail at bottom	755	-P/4 = -200	0.1	0.1	0.0	<0.1	<1:7550
		-2P/4 = -400	0.2	0.2	0.0	0.1	1:7550
		-3P/4 = -600	0.4	0.4	0.1	0.2	1:3775
		-4P/4 = -800	0.5	0.5	0.1	0.2	1:3775
		0	0.1	0.1	0.0	<0.1	<1:7550

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1

A.2 Sample Drawings




Fig.1 Drawing of Representative Sample

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1




Fig.2 Drawing of Representative Sample

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1




Fig.3 Drawing of Representative Sample

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1





Fig.4 Drawing of Representative Sample

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1





Fig.5 Drawing of Representative Sample

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1





Fig.6 Locations of Displacement Measuring Devices

Test Report

Issue Date: 2018/7/12

Intertek Report No. 180418002SHF-BP-1R1



○ : Water penetration position

Fig.7 Location of Water Penetration

Test Report

Issue Date: 2018/7/12


Intertek Report No. 180418002SHF-BP-1R1

APPENDIX: SAMPLE RECEIVED PHOTO



REPORT AUTHORIZED

When signed with physical or electronic signature, the contents of this report have been prepared and approved per Intertek's quality process in accordance with ISO 17025.



Weber Wang *Daniel Zhang*

 Name: Weber Wang Name: Daniel Zhang

 Title: Reviewer Title: Project Engineer

Revision:

NO.	DATE	CHANGES	AUTHOR	REVIEWER
180418002SHF-BP-1	2018/7/9	First issue	Daniel Zhang	Weber Wang
180418002SHF-BP-1R1	2018/7/12	Revise the written description from chinese to English on drawing	Daniel Zhang	Weber Wang