

Test Report



WIND AND WATER TEST TO THE REQUIREMENTS OF AS2047

CLIENT – CIVRO Building Technology (Guangdong)
Co.,Ltd

PRODUCT – MW65OU Awning Window

TESTED AT – AZUMA JIANGMEN BRANCH
LABORATORY

REPORTED BY – AZUMA TESTING LIMITED

REPORT NO. – AZHK251208

Issue Date: 29th December 2025

This document shall not be reproduced, except in full.

Test results in this report are relevant only to the sample tested.





A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路80号4栋101室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

1 Customer Requirements

Customer requires all applicable tests to the performance requirements of AS2047, using the test procedures from AS/NZS 4420.1.

2 Reference Standard

- AS2047 – 2014 Windows and External Glazed Doors in Buildings
- AS/NZS 4420.1 – 2016 Windows external glazed timber and composite doors - Methods of test - Test sequence, sampling and test methods

3 General Information

Test Lab/ Site No.	Azuma (Jiangmen) Testing Limited/ 26054
Address	Room 101, Building 4, 80 Longxi Road, Jianghai District, Jiangmen City, China
Date(s) of Test	26 th November 2025
Test Job Number	AZJM251128
Report Issuing Lab	Azuma Testing Limited
Test Report Number	AZHK251208

3.1 Customer & Sample Information

Customer	CIVRO Building Technology (Guangdong) Co.,Ltd
Customer's Address	No. 3, Guandi Area, Fanhu, Leping, Sanshui Central Technology Park, Sanshui District, Foshan City.
Window/Door Type	Aluminium Awning Window
Model	MW65OU
Test Sample Description	Aluminium Awning Window
Number of Sample Testing	1
Manufacturer (s)	CIVRO Building Technology (Guangdong) Co.,Ltd
Manufacturer's Address	No. 3, Guandi Area, Fanhu, Leping, Sanshui Central Technology Park, Sanshui District, Foshan City.

The above information is provided by the client. Azuma does not take liability to the accuracy of this information

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION



AZUMA

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumateesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

4 Test Result Summary

Test Method per AS/NZS 4420.1	Figures Recorded	Result for compliance with AS2047
Deflection Test	Positive – 400 Pa	Pass
	Negative – 400 Pa	Pass
Operating Force Test	160N/ 80N	Pass
Air Infiltration Test	Low	Pass
Water Penetration Resistance Test	600 Pa	Pass
Ultimate Strength Test	Positive – 1400 Pa	Pass
	Negative – 1400 Pa	Pass

* N/A: Not Applicable

** N/T : Not Tested

5 Test Sample Description

Product Name	MW65OU Awning Window
Model	MW65OU
Dimension of Frame	2700 mm (Height) x 3000 mm (Width) x 65 mm (Thickness)
Dimension of Sashes	Awning Sash: 1713.4 mm (Height) x 1113.4 mm (Width) Fixed Panel 1: 946.1 mm (Height) x 1200 mm (Width) Fixed Panel 2: 2700 mm (Height) x 1800 mm (Width)
Glazing – Size/Type	Awning Sash: 1574mm (Height) x 974mm (Width) Glass Thickness: (6mm /19A/6mm) Glass Type: Toughened Insulating Glass Unit (IGU) Supplier: Sunglas Technics Co., LTD. Fixed Panel 1: 845mm (Height) x 1145 mm (Width) Glass Thickness: (6mm /19A/6mm) Glass Type: Toughened Insulating Glass Unit (IGU) Supplier: Sunglas Technics Co., LTD. Fixed Panel 2: 2630mm (Height) x 1745 mm (Width) Glass Thickness: (6mm /19A/6mm) Glass Type: Toughened Insulating Glass Unit (IGU) Supplier: Sunglas Technics Co., LTD.
Hardware	Name: Transmission box Model No.: C722034 Quantity: 1 pc Supplier: CIVRO

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION



A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

	<p>Name: Lock bracket Model No.: C742091 Quantity: 2 pcs Supplier: CIVRO</p> <p>Name: Lock point Model No.: C742092 Quantity: 2 pcs Supplier: CIVRO</p> <p>Name: Fall protection rope Model No.: C764090 Quantity: 1pc Supplier: CIVRO</p> <p>Name: Top-Hung Hinge Model No.: C731053 Quantity: 2pcs Supplier: CIVRO</p> <p>Name: Handle Model No.: C510007 Quantity: 1pc Supplier: CIVRO</p>
Drawing Identification	XHDD-202510-0122, DY-1, C1, JD-01, J02, C01, D01, D02, D03, H19,H08, H17, H12, I01, I03, I04 & I10
Profile Section	Model: 6060T6 Manufacturer: FOSHAN YINGHUI ALUMINUM PROFILES CO., LTD. See Drawings for Details
Frame Corner Construction Details	See Drawings for Details
Drain holes	<p>Size (Width x Height): 30 X 4 mm Quantity: 2 ea</p> <p>Size (Width x Height): 45 X 7.5 mm Quantity: 6 ea</p> <p>Size (Width x Height): 30 X 8 mm Quantity: 1 ea See Drawings for Details</p>
Weep holes	None
Gasket/Seals/Hairs	None

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION



A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

Weather Strip

Model No.: C358015
Material: Foam & EPDM
Supplier: CIVRO

Model No.: C358016
Material: EPDM
Supplier: CIVRO

Model No.: 80003
Material: EPDM
Supplier: CIVRO

Model No.: C358018
Material: EPDM
Supplier: CIVRO

Model No.: C358023
Material: EPDM
Supplier: CIVRO

Model No.: C358027
Material: Foam & EPDM
Supplier: CIVRO

Model No.: C358022
Material: EPDM
Supplier: CIVRO

Model No.: 80010
Material: EPDM
Supplier: CIVRO

Model No.: C671017
Material: EPDM
Supplier: CIVRO


Glass Retention

Model No.: C358015
Material: Foam & EPDM
Supplier: CIVRO

Model No.: C358016
Material: EPDM
Supplier: CIVRO

Model No.: 80003
Material: EPDM
Supplier: CIVRO

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION



A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万 (江门市) 测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

Thermal Break	Yes Model No.: C422512 Model No.: C422510 Supplier: Technoform
Sub Head and Sub Sill Used	None
Reinforcement	None
Installation	The exterior perimeter of the test specimen was sealed with silicon sealant
Support Fixings	The test specimen and frame were fixed securely onto the test rig using screws.

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION



A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

6 Procedures

6.1 Deflection Test

1. The test sample shall be operative and pre-loaded as described in AS 4420.1.
2. The pre-load pressure shall be removed and the zero position of the displacement measuring devices recorded.
3. Differential pressures in the same direction shall then be applied across the test sample in not less than four approximately equal increments until the test pressure is reached. The pressure shall be held for at least 1 min at each pressure increment, and the readings of the displacement measuring devices recorded before the pressure is increased.
4. The differential pressure shall be removed and after 2 min the zero displacement readings shall be taken.
5. The direction of the air pump or test sample shall be reversed and Steps (1) to (4) shall be repeated using the opposite test loading.

6.2 Operating Force Test

1. With the window closed, but unlocked, an operating force shall be applied, without shock, in the plane and direction of the sash operation.
2. For both directions of sash travel, the following forces shall be noted and recorded:
 - (a) That capable of setting the sash in motion.
 - (b) That capable of maintaining the motion after the sash frame is clear of the perimeter frame of the test sample.
3. Each sliding sash of the test sample is tested separately.
4. For horizontally sliding sashes, the force shall be applied either at the position of a fixed handle, or at one-third of the height of the pull stile above the sill for continuous or adjustable handgrips.
5. For vertically sliding sashes, the force shall be applied at the sash pulls or at the midpoint of the bottom rail, or at the position nominated by the manufacturer.

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

6.3 Air Infiltration Test

1. Operation and pre-loading as described in AS 4420.1.
2. The face of the test sample shall then be sealed airtight by covering it with an impervious film. If this is not practicable, all joints, weep holes, and glazing or sealant lines of the test sample shall be sealed with impervious adhesive tape.
3. Positive and negative test pressures shall then be applied, and the base air infiltration rates through the test apparatus shall be determined by air flow meter.
4. The sealing film or tape shall be removed from the test sample and the air infiltration rates determined. The air infiltration through the test sample shall be the difference between the base and total readings.

6.4 Water Penetration Resistance Test

1. The test sample shall be subjected to water sprayed uniformly and continuously over the exterior face of the test sample at a rate not less than $0.05 \text{ L/m}^2\text{s}$. At the start of the test, the water sprays shall operate for 5 min with zero air pressure differential on the test sample.
2. The test pressure shall be applied and maintained for 15 min with the water sprays still operating. The visible internal surfaces of the test sample shall be inspected throughout the water spray operation.
3. Any water appearing on the inside surfaces of the test sample shall be noted and recorded, with the extent and, if possible, the source of penetration of uncontrolled water. Uncontrolled water shall be as defined in AS 2047.
4. The pressure and water sprays shall then be removed from the test sample.

6.5 Ultimate Strength Test

1. The test sample shall be subjected to a smoothly increasing differential pressure up to the test pressure determined in Clause 6.1, conducted individually in both positive and negative directions.
2. The time taken to reach the structural test pressure shall be approximately 1 min. Test pressure shall be maintained on the test sample for a period of 10 s.
3. If a sponsor requires incremental tests, each increment shall represent a separate test requiring 10 s duration.
4. At the conclusion of the test at each loading, the test sample shall be inspected and any signs of deformity or damage or collapse of the test sample noted and recorded.

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





7 Results

7.1 Test for Operation

- The test specimen has been opened and closed for 5 times and operates well.




Figure 1 Transducer Locations

7.2 Deflection Test

Setup 1				
Structural Member	Transom 1, 2, 3			
Span Length	1100 mm			
Transducers Used	1, 2, 3			
Maximum Allowable Deflection	4.40 mm			
Test Deflection Ratio of Sample	1 (mm)	2 (mm)	3 (mm)	Net Deflection (mm)
Positive 100 Pa	0.07	0.62	1.06	0.72
Negative 100 Pa	-0.07	-0.63	-1.11	0.76
Positive 200 Pa	0.16	1.29	2.22	1.50
Negative 200 Pa	-0.15	-1.32	-2.28	1.55
Positive 300 Pa	0.26	2.04	3.49	2.34
Negative 300 Pa	-0.28	-2.15	-3.63	2.42

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION



A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited


江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

Positive 400 Pa	0.35	2.78	4.78	3.22
Negative 400 Pa	-0.40	-2.93	-4.90	3.24
Span Ratio	Positive – 345			
	Negative – 343			
Result	Positive – Pass			
	Negative – Pass			

Setup 2

Structural Member	Awning Stile 4, 5, 6			
Span Length	1590 mm			
Transducers Used	4, 5, 6			
Maximum Allowable Deflection	6.36 mm			
Test Deflection Ratio of Sample	4 (mm)	5 (mm)	6 (mm)	Net Deflection (mm)
Positive 100 Pa	0.00	0.05	0.06	0.04
Negative 100 Pa	-0.12	-0.22	-0.22	0.05
Positive 200 Pa	0.06	0.17	0.20	0.09
Negative 200 Pa	-0.16	-0.33	-0.31	0.10
Positive 300 Pa	0.16	0.34	0.38	0.13
Negative 300 Pa	-0.30	-0.61	-0.56	0.18
Positive 400 Pa	0.26	0.50	0.57	0.19
Negative 400 Pa	-0.41	-0.85	-0.76	0.27
Positive 500 Pa	0.47	0.83	0.91	0.26
Negative 500 Pa	-0.54	-1.14	-1.00	0.37
Positive 600 Pa	0.47	0.85	0.95	0.29
Negative 600 Pa	-0.71	-1.51	-1.29	0.51
Positive 700 Pa	0.56	1.01	1.13	0.35
Negative 700 Pa	-0.91	-1.93	-1.61	0.67
Positive 800 Pa	0.69	1.20	1.35	0.41
Negative 800 Pa	-1.08	-2.32	-1.90	0.83

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION



A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路80号4栋101室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

Span Ratio	Positive – 3926
	Negative – 3120
Result	Positive – Pass
	Negative – Pass

Setup 3

Structural Member	Mullion 7, 8, 9			
Span Length	2590 mm			
Transducers Used	7, 8, 9			
Maximum Allowable Deflection	10.36 mm			
Test Deflection Ratio of Sample	7 (mm)	8 (mm)	9 (mm)	Net Deflection (mm)
Positive 100 Pa	0.23	1.09	0.23	0.86
Negative 100 Pa	-0.31	-1.29	-0.33	0.97
Positive 200 Pa	0.44	2.28	0.52	1.80
Negative 200 Pa	-0.47	-2.38	-0.57	1.86
Positive 300 Pa	0.79	3.78	0.89	2.94
Negative 300 Pa	-0.84	-3.91	-0.99	3.00
Positive 400 Pa	1.10	5.23	1.23	4.07
Negative 400 Pa	-1.07	-5.20	-1.30	4.02
Positive 500 Pa	1.56	7.11	1.76	5.45
Negative 500 Pa	-1.41	-6.65	-1.67	5.11
Positive 600 Pa	1.75	8.22	1.99	6.35
Negative 600 Pa	-1.78	-8.14	-2.05	6.23
Positive 700 Pa	2.12	9.73	2.38	7.48
Negative 700 Pa	-2.13	-9.61	-2.43	7.33
Positive 800 Pa	2.55	11.39	2.79	8.72
Negative 800 Pa	-2.44	-11.03	-2.80	8.41
Span Ratio	Positive – 297			
	Negative – 308			

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION



A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万 (江门市) 测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

Result	Positive – Pass
	Negative – Pass

7.3 Operating Force Test

Movement Type	Sash	Opening Force (N)	Closing Force (N)	Allowable (N)	Result
Initiating	1	25.58	42.17	≤ 160	Pass
Maintain	1	34.99	11.92	≤ 80	Pass

7.4 Air Infiltration Test

Barometric Pressure	102970 Pa
Air Temperature	24.7 °C
Overall Area	8.1 m ²

Pressure	Sealed	Unsealed	Net Leakage
Positive - 75 Pa	20.25 Ls ⁻¹	21.21 Ls ⁻¹	0.96 Ls ⁻¹
Negative - 75 Pa	18.68 Ls ⁻¹	20.24 Ls ⁻¹	1.56 Ls ⁻¹

Air Infiltration Level	Direction	Allowable	Actual	Result
Low	Positive	≤ 1 Ls ⁻¹ m ⁻²	0.12 Ls ⁻¹ m ⁻²	Pass
	Negative		0.19 Ls ⁻¹ m ⁻²	
High	Positive Only	≤ 5 Ls ⁻¹ m ⁻²	0.12 Ls ⁻¹ m ⁻²	Pass

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万 (江门市) 测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

7.5 Water Penetration Resistance Test

Wet Down Complete – 5 minutes	Yes
Maximum Pressure Applied to Sample	600 Pa
Time Pressure Held for	15 minutes
Leakages Observed	Nil
Observations	No Observable Water Leakage Transparent Waterproof Coating Applied Both Exterior and Interior Surfaces of Window Assembly (Figure 5,6, 8, 9, 10, 18, 19, 20, 21, 22, 26 ,27 & 31)

7.6 Ultimate Strength Test

Maximum Pressure Applied to Sample	Positive – 1400 Pa Negative – 1400 Pa
Time Pressure Held for	60 seconds
Compliant with AS2047 Clause 2.3.1.7	Yes
Observations	No Observable Damage

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION



A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

7.7 Photos



Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 2 Photo of the test specimen Before testing (Fully Closed)



Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 3 Photo of the test specimen Before testing (Fully Opened)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.






 Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 4 Photo of the test specimen After testing (Fully Close)





 Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 5 Connection Detail Between Operable Sash and Fixed Window (Left Side)

Test results in this report are relevant only to the sample tested
 NATA Accreditation Number:20513
 Accredited for compliance with ISO/IEC 17025.
 This document shall not be reproduced, except in full.





Figure 6 Connection Detail Between Operable Sash, Mullion, and Fixed Window (Middle Section)




Figure 7 Photo of Hardware (Handle)

Test results in this report are relevant only to the sample tested
 NATA Accreditation Number:20513
 Accredited for compliance with ISO/IEC 17025.
 This document shall not be reproduced, except in full.





Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 8 Connection Detail Between Mullion and Bottom Rail



Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 9 Connection Detail Between Left Side Jamb and Bottom Rail


Test results in this report are relevant only to the sample tested
 NATA Accreditation Number:20513
 Accredited for compliance with ISO/IEC 17025.
 This document shall not be reproduced, except in full.






 Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 10 Connection Detail Between Right Side Jamb and Bottom Rail




 Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 11 Photo of Awning and Fixed Window (View from Exterior) Showing Drain Holes on Transom

Test results in this report are relevant only to the sample tested
 NATA Accreditation Number:20513
 Accredited for compliance with ISO/IEC 17025.
 This document shall not be reproduced, except in full.








Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 12 Photo of Bottom Rail (Taken from Bottom-to-Top Angle) Showing Weather Strip Detail





Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 13 Awning Window in Opened Position Showing the Friction Stay Hinges (Right Side, View from Exterior)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.






Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 14 Photo of Locking Point and Locking Keeper (Right Side)





Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 15 Photo of Locking Point and Locking Keeper (Right Side)




Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 16 Photo of Locking Point and Locking Keeper (Left Side)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 17 Awning Window in Opened Position Showing the Friction Stay Hinges, Locking Point and Keeper (Left Side)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路 80 号 4 栋 101 室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk





Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 18 Awning Window in Opened Position Showing the Friction Stay Hinges, Locking Point and Keeper (Right Side)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





Figure 19 Connection Detail of Left Side Jamb, Head Jamb, and Operable Sash (Opened Position)



Figure 20 Connection Detail of Mullion, Head Jamb, and Operable Sash (Opened Position)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.







 Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 21 Photo of Mullion





 Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 22 Connection Detail of Mullion and Bottom Sill

Test results in this report are relevant only to the sample tested
 NATA Accreditation Number:20513
 Accredited for compliance with ISO/IEC 17025.
 This document shall not be reproduced, except in full.






 Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 23 Photo of Upper Section of Window Assembly (View from Exterior)





 Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 24 Photo of Lower Section of Window Assembly (View from Exterior)

Test results in this report are relevant only to the sample tested
 NATA Accreditation Number:20513
 Accredited for compliance with ISO/IEC 17025.
 This document shall not be reproduced, except in full.







Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 25 Photo of Middle Section of Window Assembly (View from Exterior)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.






Figure 26 Corner Detail Between Top Rail and Stile of Operable Sash (Left Side, View from Exterior)



Figure 27 Corner Detail Between Top Rail and Stile of Operable Sash (Right Side, View from Exterior)

Test results in this report are relevant only to the sample tested
 NATA Accreditation Number:20513
 Accredited for compliance with ISO/IEC 17025.
 This document shall not be reproduced, except in full.








Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 28 Photo of Operable Sash in Open Position (View from Side and Exterior)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.







Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 29 Photo of Operable Sash in Open Position (View from Bottom and Exterior) Showing Detail of Hardware – Locking points and Handle

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 30 Photo of Operable Sash in Open Position (View from Bottom and Exterior) Showing Detail of Hardware – locking points & Limit Stay

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



Figure 31 The Bottom Sill of Window Assembly (View from Exterior)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路80号4栋101室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

8 Signatories

Tested By: **Dennis Chu**

Signature:

Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Date:

12/29/2025

Checked By:


George Cheung

Signature:

Cheung George (Dec 29, 2025 15:44:11 GMT+8)

Date:

12/29/2025



Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





A Z U M A

Test Report

東方檢測有限公司
Azuma Testing Limited

香港新界沙田火炭山尾街 43-47 號環球工業中心地下 6 號
Workshop No. 6, G/F, World-wide Industrial Centre,
43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong
W: www.azumatesting.com

P: +852 2494 7370

澳思万(江门市)测试有限公司
Azuma (Jiangmen) Testing Limited

江门市江海区龙溪路80号4栋101室
Room 101, Building 4, 80 Longxi Road
Jianghai District, Jiangmen City, China
M: info@azuma.com.hk

9 Appendix (Drawings supplied by customer)



Figure 32 Drawing of Inspection Product Sample, MW650U Design Proposal Drawing, Design No.: XJDD-202510-0122

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.







Figure 33 Drawing of Interior View

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.







Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 34 Drawing of Hinge-Side Steel Test Frame Fabrication

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.






Figure 35 Drawing of the Representative Sample (view from Interior)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number: 20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.






Figure 36 Drawing of Hardware Fitting


Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



CIVRO.
Windows & Facades System

MW650U Awning Window Profile and Hardware Summary

Introduction to Aluminum Profiles



Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)


MW650U Awning Window System Product Technical Manual C01


Figure 37 Drawing of MOW650U To Hung Window Profiles and Hardware Summary

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



CIVRO.
Windows & Facades System




Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Introduction to Aluminum Profiles

C01

MW650U Awning Window System Product Technical Manual

Figure 38 Drawing of Profile Section Details

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



Name	Material	Notes	Name	Material	Notes
C671022 φ9 Process hole cap	Decorate		C358018 Stopper rubber strip	Foaming+EPDM	Frame and sash sealing
C358015 Outside rubber strip	Foaming+EPDM	Glass encapsulation	80003 Inside rubber strip	EPDM	Glass encapsulation
C358016 Inside rubber strip	EPDM	Glass encapsulation	C358022 Foaming rubber rod	Foaming	Sealing strip
C671014 C-shaped cover plate	PVP Hard rubber strip	Decorate	80010 Inside rubber strip	EPDM	Glass encapsulation
C358027 Middle rubber strip	Foaming+EPDM	Frame and sash seal	C671019 T-shaped connection seal component	PA6	T-shaped connection seal
C358023 The third rubber strip	EPDM	Door threshold sealing	C671018 T-shaped connection seal component	PA6	T-shaped connection seal
C311042 Sealing gasket	Sponge Seal		C671017 Middle rubber strip connect	EPDM	Connected middle rubber strip
C671017 Middle rubber strip connect	EPDM	Connected middle rubber strip	C671016 T-shaped connection seal component	PA6	T-shaped connection seal
C671016 T-shaped connection seal component	PA6	T-shaped connection seal	C671015 T-shaped connection seal component	PA6	T-shaped connection seal
C671015 T-shaped connection seal component	PA6	T-shaped connection seal	C671014 T-shaped connection seal component	PA6	T-shaped connection seal
C671014 T-shaped connection seal component	PA6	T-shaped connection seal	C671013 T-shaped connection seal component	PA6	T-shaped connection seal
C671013 T-shaped connection seal component	PA6	T-shaped connection seal	C671012 T-shaped connection seal component	PA6	T-shaped connection seal
C671012 T-shaped connection seal component	PA6	T-shaped connection seal	C671011 T-shaped connection seal component	PA6	T-shaped connection seal
C671011 T-shaped connection seal component	PA6	T-shaped connection seal	C671010 T-shaped connection seal component	PA6	T-shaped connection seal
C671010 T-shaped connection seal component	PA6	T-shaped connection seal	C671009 T-shaped connection seal component	PA6	T-shaped connection seal
C671009 T-shaped connection seal component	PA6	T-shaped connection seal	C671008 T-shaped connection seal component	PA6	T-shaped connection seal
C671008 T-shaped connection seal component	PA6	T-shaped connection seal	C671007 T-shaped connection seal component	PA6	T-shaped connection seal
C671007 T-shaped connection seal component	PA6	T-shaped connection seal	C671006 T-shaped connection seal component	PA6	T-shaped connection seal
C671006 T-shaped connection seal component	PA6	T-shaped connection seal	C671005 T-shaped connection seal component	PA6	T-shaped connection seal
C671005 T-shaped connection seal component	PA6	T-shaped connection seal	C671004 T-shaped connection seal component	PA6	T-shaped connection seal
C671004 T-shaped connection seal component	PA6	T-shaped connection seal	C671003 T-shaped connection seal component	PA6	T-shaped connection seal
C671003 T-shaped connection seal component	PA6	T-shaped connection seal	C671002 T-shaped connection seal component	PA6	T-shaped connection seal
C671002 T-shaped connection seal component	PA6	T-shaped connection seal	C671001 T-shaped connection seal component	PA6	T-shaped connection seal
C671001 T-shaped connection seal component	PA6	T-shaped connection seal	C671000 T-shaped connection seal component	PA6	T-shaped connection seal






Figure 39 Drawing of Accessory Components 1 (Details of Gasket)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



Substrate Materials Introduction

MW650U Awning Window System Product Technical Manual D01

				
<p>Name C72601 Material PVC</p>	<p>Name C551024 Material 6063-T5</p>	<p>Name C551023 Material 6063-T5</p>	<p>Name C670158 Material PA6</p>	<p>Name C553021 Material 304 Stainless steel</p>
<p>Notes C-shaped transmission</p>	<p>Notes T connection</p>	<p>Notes T connection</p>	<p>Notes Drainage Decorate</p>	<p>Notes Frame and sash corner connection</p>
<p>Name G55122-1500 Material 6063-T5</p>	<p>Name G671029 Material PA6</p>	<p>Name G671028 Material PA6</p>	<p>Name G671043 Material PVC</p>	<p>Name G671042 Material PVC</p>
<p>Notes Corner connection of the frame</p>	<p>Notes With G621103/03 angle bracket</p>	<p>Notes With G621101, G621102/01 angle brackets</p>	<p>Notes Adjustable glass</p>	<p>Notes Glazing</p>
<p>Name G55121-1500 Material 6063-T5</p>	<p>Name G55122-1300 Material 6063-T5</p>	<p>Name G55124-1300 Material 6063-T5</p>	<p>Name G55125-1500 Material 6063-T5</p>	<p>Name G55122-1300 Material 6063-T5</p>
<p>Notes Corner connection of the convert frame</p>	<p>Notes Corner connection of the convert frame</p>	<p>Notes Window sash corner connection</p>	<p>Notes Window sash corner connection</p>	<p>Notes Corner connection of the frame</p>






Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)


Figure 40 Drawing of Accessory Components 2 (Details of Drain Hole Cover, Hardware and Others)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





				
Name: C754082 Frame climbing block	Name: C754083 Window sash climb block	Name: C67104 Green glass spacer block	Name: C501016 Top screw	Name: C500029 05*16 Cotter pin
Material: Anti-sagging	Material: Anti-sagging	Material: Glass installation	Material: Fixed connector piece	Material: Fixed connector
Notes: Anti-sagging	Notes: Anti-sagging	Notes: Glass installation	Notes: Fixed connector piece	Notes: Fixed connector


Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Substrate Material Introduction

D03







MW650U Awning Window System Product Technical Manual


Figure 41 Drawing of Accessory Components 3 (Details of Fastener and Others)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



CIVRO.
Windows & Facades System

Name	Brand	Code	Name	Brand	Code	Name	Brand	Code
Transmission box	CIVRO	C722034	Lock bracket	CIVRO	C742091	Lock point	CIVRO	C742092
								
	CIVRO	C731053	Handle	CIVRO	C510007			
	CIVRO	C754090						


Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Introduction to Aluminum Profiles

C01

MW650U Awning Window System Product Technical Manual

Figure 42 Drawing of Hardware

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



CIVRO.
Windows & Facades System

CR156001 Frame fan
Die forming process







Illustration of the positions for injection, ventilation and drainage of the window sash



Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)



Standard processing drawing


H19

MW650U Awning Window System Product Technical Manual

Figure 43 Drawing of Operable Sash Frame with Drainage System Details

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





Standard processing drawing

H08

MW650U Awning Window System Product Technical Manual


Figure 44 Drawing of Bottom Rail with Drainage System Details

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

CIVRO
Windows & Facades System



H12 MW650U Awning Window System Product Technical Manual

Standard processing drawing

Figure 46 Drawing of Transom with Drainage System Details

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.







Figure 47 Drawing of Frame Corner Construction (Main Frame)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)



Assembly and Process Diagram

I03

MW650U Awning Window System Product Technical Manual

Figure 48 Drawing of Frame Corner Construction (Connection between Mullion and Head or Lamb)


Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.



WORLD RECOGNISED
ACCREDITATION

CIVRO.
Windows & Facades System

Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)



MW650U Awning Window System Product Technical Manual


104

Assembly and Process Diagram

Figure 49 Drawing of Frame Corner Construction (Transom and Mullion Connection)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.





Assembly and Process Diagram



I10

MW650U Awning Window System Product Technical Manual

Figure 50 Drawing of Frame Corner Construction (Sash Frame)

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.







Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 51 Drawing of Cross-section of Top and Bottom Rails

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.







Dennis Chu (Dec 29, 2025 17:00:34 GMT+8)

Figure 52 Drawing of Cross-section of Sash Frame Corners

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.






Figure 53 Drawing of Glazing

Test results in this report are relevant only to the sample tested
 NATA Accreditation Number:20513
 Accredited for compliance with ISO/IEC 17025.
 This document shall not be reproduced, except in full.

END OF REPORT

Please note that this report is issued under the following terms:

1. This report applies to the sample of the specific product/equipment given at the times of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar, supplier or user of such product/equipment, or that AZUMA HONG KONG in any way “guarantees” the later performance of the product/equipment. Unless otherwise stated in this report, no tests were conducted to determine long term effects of using the specific product/equipment.
2. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. AZUMA HONG KONG therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
3. Nothing in this report shall be interpreted to mean that AZUMA HONG KONG has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
4. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to AZUMA HONG KONG or to the report or results furnished by AZUMA HONG KONG in any advertisements or sales promotion.
5. Unless otherwise stated, the tests were carried out in AZUMA TESTING LTD, Workshop No.6, World-Wide Industrial Centre, 43-47 Shan Mei Street, Fotan, Hong Kong

Test results in this report are relevant only to the sample tested
NATA Accreditation Number:20513
Accredited for compliance with ISO/IEC 17025.
This document shall not be reproduced, except in full.

